


NYLON-INSULATED RING TERMINALS 尼龙圆型绝缘端子



PART NO 2015-2018	ITEM NO	WIRE RANGE		DIMENSIONS						COLOR
		AWG/MCM	mm ²	ΦE	ΦD	Φd	W	B	L	
LY0021-2001	NL1.25-3	22-16	0.25-1.65	3.7	4.3	1.7	5.5	11.3	18.2	RED
LY0021-2002	NL1.25-3A			3.2	4.3	1.7	5.5	11.3	18.2	
LY0021-2003	NL1.25-3M			3.7	4.3	1.7	6.6	11.3	21.2	
LY0021-2004	NL1.25-4			4.3	4.3	1.7	8.0	11.3	22.7	
LY0021-2005	NL1.25-4M			4.3	4.3	1.7	6.6	11.3	21.2	
LY0021-2006	NL1.25-5			5.3	4.3	1.7	8.0	11.3	22.7	
LY0021-2007	NL1.25-6			6.4	4.3	1.7	11.6	11.3	28.4	
LY0021-2008	NL1.25-8			8.4	4.3	1.7	11.6	11.3	28.4	
LY0021-2009	NL1.25-10			10.5	4.3	1.7	13.6	11.3	32.7	
LY0021-2010	NL2-3			16-14	1.04-2.63	3.7	4.6	2.3	8.5	
LY0021-2011	NL2-3A	3.2	4.6			2.3	8.5	11.3	23.2	
LY0021-2012	NL2-3M	3.7	4.6			2.3	6.6	11.3	20.7	
LY0021-2013	NL2-4	4.3	4.6			2.3	8.5	11.3	23.2	
LY0021-2014	NL2-4M	4.3	4.6			2.3	6.6	11.3	20.7	
LY0021-2015	NL2-5	5.3	4.6			2.3	9.5	11.3	23.2	
LY0021-2016	NL2-6	6.4	4.6			2.3	12.0	11.3	28.2	
LY0021-2017	NL2-8	8.4	4.6			2.3	12.0	11.3	28.2	
LY0021-2018	NL2-10	10.5	4.6			2.3	13.6	11.3	31.7	
LY0021-2019	NL5.5-3	12-10	4.60-6.64	3.7	6.6	3.5	9.5	14.1	27.1	YELLOW
LY0021-2020	NL5.5-4			4.3	6.6	3.5	9.5	14.1	27.1	
LY0021-2021	NL5.5-5			5.3	6.6	3.5	9.5	14.1	27.1	
LY0021-2022	NL5.5-6			6.4	6.6	3.5	12.0	14.1	33.1	
LY0021-2023	NL5.5-6S			6.4	6.6	3.5	12.0	14.1	29.8	
LY0021-2024	NL5.5-8			8.4	6.6	3.5	15.0	14.1	35.1	
LY0021-2025	NL5.5-10			10.5	6.6	3.5	15.0	14.1	35.1	
LY0021-2026	NL8-3	8	6.64-10.52	3.7	8.0	4.5	10.0	29.0	29.0	RED
LY0021-2027	NL8-4			4.3	8.0	4.5	10.0	29.0	29.0	
LY0021-2028	NL8-5			5.3	8.0	4.5	10.0	29.0	29.0	
LY0021-2029	NL8-6			6.4	8.0	4.5	10.0	29.0	30.5	
LY0021-2030	NL8-8			8.4	8.0	4.5	14.0	29.0	35.0	
LY0021-2031	NL8-10			10.5	8.0	4.5	18.0	29.0	38.0	
LY0021-2032	NL8-12			13.0	8.0	4.5	18.0	29.0	38.0	